



TECHNICAL DATA SHEET

Order reference	ENV100-M
Article number	813741

Date	4-11-11	Replaces	31-06-06	No. Pages	1
-------------	---------	-----------------	----------	------------------	---

Product Description:

Style	Pads
Item Size (each)	41 cm x 51 cm
Color	White
Composition	100% Polypropylene
Structure	Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]
Technology	Meltblown, 1-ply MAXX™ TECHNOLOGY
Absorbency	Hydrophobic + Oleophilic
Bonding	Mechanical entanglement

Intended Application	Chemical Resistant Sorbent for Oil & Solvent Base Liquids
-----------------------------	---

Absorbency Capacity	136 l per bale (saturated; medium viscosity-20x)
----------------------------	--

Packaging Description:

Package configuration	1 Case	Pkg. Weight	7.1 kg (5.9 kg)
Items per Package	100 Pads/Case	Pkg. Dimensions	53cm x 43cm x 44cm H
Container type	Carton		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002	G/M2	280	28
Caliper	SPCTM-020	mm	7.0	0.7
Absorbency** (med.visc.)	SPCTM-004B	gL/gS	20	2
Tensile Strength	SPCTM-007	daN	5.8	0.5
Color	Visual	-----	White	per standard

The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.