



TECHNICAL DATA SHEET

Order reference	ENV152-E
Article number	813762

Date	4-11-11	Replaces	03-06-07	No. Pages	1
-------------	---------	-----------------	----------	------------------	---

Product Description:

Style	Blanket roll
Item Size (each)	48 cm x 44 m
Color	White
Composition	100% Polypropylene
Structure	Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]
Technology	Meltblown, 1-ply
Absorbency	Hydrophobic + Oleophilic
Bonding	Mechanical entanglement

Intended Application	Chemical Resistant Sorbent BLANKET for Oil & Solvent Based Liquids
-----------------------------	---

Absorbency Capacity	274 l per bale (saturated; medium viscosity-20x)
----------------------------	--

Packaging Description:

Package configuration	bale	Pkg. Weight	12.0 kg (11.8kg)
Items per Package	2-rolls/bale	Pkg. Dimensions	47cm x 47cm x 97cm H
Container type	Polybag + Twist Tie		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002A	G/M2	280	28
Caliper	SPCTM-020	mm	7.0	0.7
Absorbency** (med.visc.)	SPCTM-004B	gL/gS	20	2
Tensile Strength	SPCTM-007	daN	5.8	0.5
Color	Visual	-----	White	per standard

The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium |
 Tel: +32 52.45.7811 | Fax: +32 52.45.7812
 www.bradyeurope.com