



TECHNICAL DATA SHEET

Order reference	RFP500
Article number	813943

Date	17-10-08	Replaces	new	No. Pages	1
-------------	----------	-----------------	-----	------------------	---

Product Description:

Style	Pads , perforated on centerline for dividing in half for smaller applications.
Item Size (each)	38 cm x 48 cm
Color	Off-white
Composition	99% cellulose 1% spunbond
Structure	2-ply – Nonwoven mat of randomly oriented cellulose fibers
Absorbency	Hydrophilic + Oleophilic
Bonding	Mechanical entanglement

Intended Application	Sorbent for Water, Oil, or Solvent Base Liquids
-----------------------------	---

Absorbency Capacity	90 l per bale (saturated; medium viscosity-12.5x)
----------------------------	---

Packaging Description:

Package configuration	1-Case	Pkg. Weight	5.8 kg (4.9 kg)
Items per Package	100-Pads/Case	Pkg. Dimensions	51 cm x 41 cm x 43cm H
Container type	Carton		

Physical Properties:

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002A	G/M2	265	26
Caliper	SPCTM-020	mm	5.1	0.5
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	16.5	1.6
Tensile Strength	SPCTM-007	daN	8.2	0.8
Color	Visual	-----	Off-white	per standard

The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.