



TECHNICAL DATA SHEET

| | |
|------------------------|---------------|
| Order reference | SPC10 |
| Article number | 813783 |

| | | | | | |
|-------------|---------|-----------------|---------|------------------|---|
| Date | 4-11-11 | Replaces | 3-20-01 | No. Pages | 1 |
|-------------|---------|-----------------|---------|------------------|---|

Product Description:

| | |
|-------------------------|---|
| Style | Pillow |
| Item Size (each) | 36 cm wide x 64 cm long |
| Color | White Particulate inside a Red Netting Sack with a tie string |
| Composition | 100% Polypropylene |
| Technology | Meltblown |
| Absorbency | Hydrophobic + Oleophilic |

| | |
|-----------------------------|--|
| Intended Application | Chemical Resistant Sorbent Pillow Spills of Oil Base or Solvent Base Liquids |
|-----------------------------|--|

| | |
|----------------------------|---|
| Absorbency Capacity | 197 l per bale (saturated; medium viscosity- 12.5x) |
|----------------------------|---|

Packaging Description:

| | | | |
|-----------------------|---------------------|---------------------------|-------------------|
| Package configuration | Bale | Pkg. Weight | 13.8 kg (13.6 kg) |
| Items per Package | 10 Pillows/Bale | Pkg. Dimensions (approx.) | Ø 51cm x 102 cm H |
| Container type | Polybag & Twist-tie | | |

Physical Properties:

| <u>Parameter</u> | <u>SPC Test Method</u> | <u>Units</u> | <u>Nominal</u> | <u>(+/-)Tolerance</u> |
|-----------------------|------------------------|--------------|--------------------|-----------------------|
| Pillow Weight | Gravimetric | kg | 13.6 | 0.22 |
| Absorbency (med. oil) | SPCTM-012B | gL/gS | 12.5 | 11-min. |
| Color | Visual | ----- | Red net/White fill | per standard |

The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

**** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

| | |
|----------------------|--|
| Attributes | Product will be free of foreign material contamination, rips, holes, and tears. |
| Labeling | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code). |
| Certification | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |