



**TECHNICAL DATA SHEET**

<b>Order reference</b>	<b>SPCJR-1205</b>
<b>Article number</b>	<b>813806</b>

<b>Date</b>	11-14-06	<b>Replaces</b>	New	<b>No. Pages</b>	1
-------------	----------	-----------------	-----	------------------	---

**Product Description:**

<b>Style</b>	Contractor Boom
<b>Item Size (each)</b>	15 cm Float, 30 cm Skirt, total length = 15m, floatation length 1.8m
<b>Composition</b>	Vinyl coated Polyester PVC 745 gr/m <sup>2</sup>
<b>Structure</b>	Floatation material wrapped in cylindrical tubes with a Vinyl coated Polyester PVC fabric skirt hanging into the water held down by a tension member inside the bottom of the skirt to prevent under flow of oil.
<b>Connections</b>	Universal Aluminum or ASTM "Z" type
<b>Tension Member</b>	6mm hot dip galvanized chain
<b>Color</b>	International Yellow
<b>Cleaning</b>	Industrial detergents, steam, pressure wash, etc.
<b>Absorbency</b>	No absorbency

<b>Intended Application</b>	Containment barrier of oil on water in rivers and harbors at a wave height of max 1 meter or wind speed of 28-37 km/hr
-----------------------------	--

**Packaging Description:**

Package configuration	Geotextile	Pkg. Weight	37.5 kg
Items per Package	1 Boom	Pkg. Dimensions	185 cm x 37,5 cm x 75 cm
Container type	Geotextile		

**Physical Properties:**

<u>Parameter</u>		<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Total tensile strength		daN	2273	
Temperature range		°C	-34°C to +60°C	
Color	Visual	-----	International Yellow	per standard

**The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.**

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
<b>Certification</b>	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.